DUCHESNE COUNTY MONUMENT SURVEY RECORD

17.48.40.,

>

T1S R3W

SEC 16 | SEC 15

SEC 21 SEC 22

U.S.B.&M. N - 13

21

FOUND AN ALUMINUM
DUCHESNE COUNTY MONUMENT AT 1/4 CORNER


N 89°59'23" W

2642.28'

66.11'09" E 131.3 66.11'09" E PIPE TO FACE OFNER FENCE CORNER


NOTE:

'THE BASIS OF BEARINGS IS GEODETIC NORTH DERIVED FROM G.P.S. OBSERVATIONS AT A CONTROL POINT (SECTION CORNER) LOCATED AT LAT. 40°21'33.88695"N AND LONG. 110°13'06.20894"W USING THE UTAH STATE G.P.S. VIRTUAL REFERENCE STATION CONTROL NETWORK MAINTAINED AND OPERATED BY THE AUTOMATED GEOGRAPHIC REFERENCE CENTER



NAIL AND WASHER ON EAST SIDE OF FENCE CORNER

FOUND A REBAR WITH A 2½" ALUMINUM DUCHESNE COUNTY MONUMENT AT 1/4 CORNER



SCALE: 1"=30'



DESCRIPTION OF CORNER EVIDENCE FOUND

FOUND AN ALUMINUM DUCHESNE COUNTY PIPE MONUMENT AT THE POSITION OF THE SECTION CORNER

DESCRIPTION OF MONUMENT AND ACCESSORIES ESTABLISHED TO PERPETUATE THE ORIGINAL LOCATION OF THE CORNER

FACE OF PIPE OF FENCE CORNER

RESET MONUMENT AFTER ROAD CONSTRUCTION



STATE PLANE COORDINATE DATA

(U.S. SURVEY FEET) NAD83 UTAH CENTRAL ZONE N: 7312764.259

E: 1997414.568 NAVD88 EL: 6309.91'

LATITUDE: 40°23'18.24584" N

LONGITUDE: 110°13'06.04239" W ELLIPSOID HEIGHT: 6256.72'

(GEOID 03 CONUS)

PUBLIC LAND SURVEY SYSTEM GCDB ID NO.

UT300010S0030W0_400400





CERTIFICATION

Jerry D. Allred _ , Professional Land Surveyor, State of Utah, do hereby certify that I have performed or reviewed the work done on the diagrammed corner as reported on this recordation form and approve same

FACE OF PIPE FENCE CORNER

Date <u>28 FEB</u> 2018

Jerry D. Allred, Professional Land Surveyor Certificate No. 148951 Duchesne County Surveyor

